



ENGINE

TYPE DISPLACEMENT MAX POWER MAX TOROUF STARTING IGNITION SPARK PLUG LUBRICATION

4 STROKE, LIQUID COOLED, SI ENGINE 225 8 CC

7.5 KW @ 4750 RPM 18 NM @ 2750 RPM **ELECTRIC & HAND START** TRANSISTOR CONTROLLED BOSCH URGDE FORCED WET SUMP WITH CHAIN

DRIVEN OIL PUMP

TRANSMISSION

4 FORWARD & 1 REVERSE INTEGRATED NO. OF GEARS **FORWARD & REVERSE GEAR**

GEAR BOX TYPE TYPE

MANUAL, CONTANT MESH FORK & CAM DRUM SHIFT MECHANISM

CLUTCH

TYPE WET/DRY

WET MULTIPLATE, HAND OPERATED

CHASSIS TYPE

SEMI MONOCODUE CHASSIS MADE OF PRESSED LONGITUDINAL AND CROSSED MEMBERS

BRAKES

FRONT & REAR PARKING BRAKE DRUM HYDRAULIC HAND OPERATED MECHANICAL REAR BRAKES, EXPANDING SHOE TYPE

SUSPENSION

FRONT

REAR

TRAILING ARM TYPE CO-AXIAI-CONSTANT RATE HELICAL COIL SPRING TRAILING ARM INDEPENDENT SPRING REAR WHEELS CONSTANT RATE HELICAL COIL SPRING.

HYDRAULIC DOUBLE ACTING SHOCKARSORRER

WHEELS & TYRES

TYRE SIZE FRONT & REAR 4.00 - 8.6 PR

ELECTRICAL

BATTERY HEAD LAMP WARNING LAMP

DIMENSION, WEIGHTS & CAPACITIES

WHEEL BASE OVERALL LENGTH **OVERALL WINTH** OVERALL HEIGHT KERB WEIGHT **GROUND CLEARANCE** FUEL TANK CAPACITY 12 V 32 AH 35/35 LOW OIL PRESSURE. COOL ANT HIGH TEMPARATURE

1990MM 2645 MM 1330 MM 1740 MM 356 KG **LADEN - 169 MM**

7.5 + 0.5 (PETROL)

GRADEABILITY

VEHICLE SPEED

65 + 2 KMPH*

SEATING CAPACITY

DRIVER + 3

WARRANTY





NEWEST FEATURES



LIQUID COOLED ENGINE



225 CC





NEW DASHBOARD DESIGN



NOISELESS KILL & START



DRIVER STORAGE SEAT



HIGHER PULLING CAPACITY



NEW STYLISH LOGO & FENDER