



125EE-THE WICKED RIDE



MICKED FEATURES













125EE-THE WICKED RIDE

TECHNICAL SPECIFICATIONS

1 - 0	TOALO	MODION
VIII X.		MISSION
VI (V		

ENGINE & TRANSMISSION	
Туре	Air & Oil cooled single cylinder, SI
Bore x Stroke (mm)	53.5 x 55.5
Piston Displacement (cc)	124.8
No. of Valves	3
Maximum Power in kW	8.37 @ 7500 RPM
Maximum Torque in Nm	11.2 @ 6000 RPM
No. of Gears	5 Speed
Pattern	1-N-2-3-4-5
CHASSIS DIMENSIONS & WEIGHT	
Overall Length(mm)	2070
Overall Height(mm)	1028
Overall Width(mm)	785
Wheel Base(mm)	1326
Ground Clearance(mm)	180(unladen)
Kerb Weight(kg)	123
SUSPENSION	
Front Type	Telescopic

Rear Type Monoshock, 5-step adj, Gas charged

TYRES

80/100 - 17 Tubeless, 46P Front Tyre 100/90 - 17 Tubeless, 55P Rear Tyre

BRAKES

Front Disc/Drum(mm) Disc - 240, Drum - 130

Rear Drum(mm) 130 SBT

ELECTRICALS

Battery Type & Spec MF Battery, 12V 4Ah

Headlamp LED **LED** Tail Lamp

CAPACITIES Fuel Tank(Litre) 10





ETG LOGISTICS AUTOMOTIVE DISTRIBUTION c/o Scale End and Old Pretoria Road, Halfway House Estate Midrand, 1685, South Africa

Tel: +27 65 138 4567 www.tvsmotor.com/en/za